

GAC 7kW, GAC 11kW, GAC 22kW



Compact and Beautiful Design

A refined, modular design that blends functionality with a clean, professional look, adaptable for various user requirements.

Easy to Operate

Supports multiple charging options with simple app connectivity and easy switching for hassle-free use.

Safety and Durable

Equipped with IP55 waterproofing, fire-resistant materials, and comprehensive safety features for lasting performance.

Innovation

Quick to install, low maintenance, and designed with easy-access panels for effortless upkeep.

	Model	GDC 07-22K		
		1P + N + PE	3P + N + PE	3P + N + PE
Input Parameter	Rated Voltage	230 VAC + 10%	380 VAC + 10%	380 VAC + 10%
	Frequency	50 HZ / 60 HZ		
	Number of output ports	1		
Output Parameter	Rated Voltage	230 VAC + 10%	380 VAC + 10%	380 VAC + 10%
	Rated Current	16A, 32A, or 50A		
	Rated Power	7.4Kw	11kw	22kw
Safety	Electrical Protection	Over/under voltage protection, Overcurrent protection, Short circuit protection, Over temperature protection, Lightning protection, ground protection.		
	RCD	Type A+6mA DC		
	Protection Level			
	Impact Protection	IP55		
	Certifications	IK10 (display is IK08)		
	Standards	CE		
Communication	Operating Temperature	IEC61851-1/-2, IEC62196-1/-2, SAE J1772		
	Storage Temperature	-25°C to +55°C		
	Altitude	40°C to +70°C		
	Humidity	<2000m		
	Energy Metering	5-95% non-condensing		
Basic Parameter	HMI	Accuracy Class 1.0 energy meter		
	Plug Cable Length	4.3 inch LCD		
	Communication	5m		
	Protocol	Bluetooth/WiFi/Ethernet/4G LTE(Optional)		
	Connector Type	OCPP-1.6(JSON)		
	Installation Method	Type 2 GB/T Type1		
	Shell Colour	Wall-mount/column-mount		
	Shell Material	Metallic grey		
	Start Mode	(ABS+PC)-Blend		
	Place of Installation	RFID Card/QR Code/Password		
	Product Dimensions (W*H*D)	Indoor/Outdoor		
	293*140*418mm / 359*140*510mm			